



GALLERIA

PROFESSIONAL

UK FLOORING DIRECT



Product Data Sheet

ENG-GA-15-128

Scan the QR code for fast access to this floor online

Galleria Professional Engineered European Rustic Oak Flooring 15mm X 220mm Brushed & Oiled

A truly stunning traditional-style floor with a beautiful natural tone that highlights organic oak in all its glory, Galleria Professional Engineered European Rustic Oak Flooring 15mm X 220mm Brushed & Oiled is ideal for creating a grand, elegant look in spacious rooms.

Made from quality European oak in a rustic grade characterised by lively grain patterns, small mineral streaks, sapwood and multiple knots, the boards have been brushed to add texture and enhance the grain and given an oil finish for a truly authentic and unmistakable wood feel that's easy to keep clean with regular vacuuming and damp mopping.

Suited to large, grand rooms, the extra-wide, extra-long planks (220mm x 2200mm) make the most of the beauty and elegance of wood for a majestic, timeless look. Promising a lifetime of good looks Galleria Professional Engineered European Rustic Oak Flooring 15mm X 220mm Brushed & Oiled features a multi-layer construction for enhanced stability while a premium 4mm wood wear layer that gives true depth and definition to the grain. For best results, we recommend this load-bearing tongue-and-groove floor is fitted by a professional.

Product Details

Code:	ENG-GA-15-128
Brand:	Galleria Professional
Construction:	Engineered 3-Ply
Species:	Oak
Grade:	Rustic
Design:	Plank
Surface:	Brushed
Finish:	Oiled
Profile:	Tongue & Groove
Edge profile:	Bevelled on 4 sides
Top layer:	4mm
Core:	Softwood
Thickness:	15mm
Width:	220mm
Length:	2200mm
Coverage per pack:	2.90m ²

Warranty

Residential:	N/A
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

Installation

Fully-bonded:	Yes
Nailed:	Yes
Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Max side of sound knots:	50mm diameter
Max size of broken knots:	Unlimited
Sapwood:	Acceptable up to 20% of the board
Filler & colour variation:	Allowed
Small cracks:	Acceptable up to 3mm wide & 150mm long
Inner bark:	Allowed
Origin of timber:	Europe
Responsible certification:	N/A
Janka hardness rating:	1360

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.