



# GALLERIA

## PROFESSIONAL

UK **FLOORING** DIRECT



### Product Data Sheet

**ENG-GA-15-142**

Scan the QR code for fast access to this floor online

## Galleria Professional Engineered European Rustic Oak Flooring 15mm x 190mm Hickory Brown Oiled

A characterful, deep and inviting brown hue, highlighted with a silvery white running through its natural wood grain, brings this engineered wood floor a stance that feels fresh and full of attitude. The perfect addition to homes looking for a modern twist on wood flooring.

Galleria Professional Engineered European Rustic Oak Flooring 15mm x 190mm Hickory Brown Oiled is made from quality European oak using a rustic grade featuring knots, sapwood, mineral streaks and colour variation for a floor that's rich in organic appeal. Sanded smooth for a clean, modern look and UV oiled for a natural matt finish, the floor comes in a long (1900mm), wide (190mm) plank that works best in large rooms. A bevel on all four edges adds definition and gives a classic wood floor. Featuring an engineered wood three-ply construction that's great value, Galleria Professional Engineered European Rustic Oak Flooring 15mm x 190mm Hickory Brown Oiled comes with a lasting 4mm wear layer.

With occasional vacuuming and damp mopping, this style will continue to look good. A traditional T&G joint means that gluing or nailing to ensure a secure joint and so this floor is best for professional installation.

### Product Details

Code:	ENG-GA-15-142
Brand:	Galleria Professional
Construction:	Engineered 3-Ply
Species:	Oak
Grade:	Rustic
Design:	Plank
Surface:	Smooth
Finish:	UV Oiled
Profile:	Tongue & Groove
Edge profile:	Bevelled on 4 sides
Top layer:	4mm
Core:	Softwood
Thickness:	15mm
Width:	190mm
Length:	1900mm
Coverage per pack:	2.17m <sup>2</sup>

### Warranty

Residential:	N/A
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

### Installation

Fully-bonded:	Yes
Nailed:	Yes
Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

### Technical

Max side of sound knots:	50mm diameter
Max size of broken knots:	Unlimited
Sapwood:	Acceptable up to 20% of the board
Filler & colour variation:	Allowed
Small cracks:	Acceptable up to 3mm wide & 150mm long
Inner bark:	Allowed
Origin of timber:	Europe
Responsible certification:	N/A
Janka hardness rating:	1360

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.