



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Scan the QR code for fast access to this floor online

Product Data Sheet

VIN-CLIC-PL-607

Spectra Luxury Rigid Core Click Vinyl Flooring Pearl Oak Plank

Invest in Spectra Luxury Rigid Core Click Vinyl Flooring Pearl Oak Plank - a floor that truly combines unparalleled design, incredible strength, and high comfort.

Made with a tough and durable top layer for incredible protection against unwanted stains and scratches, so your dream floor will stay looking its best for longer. The wide, classic-length planks (231mm x 1535mm) will look fantastic in a wide range of spaces but are particularly well suited to creating a space-enhancing effect in small and medium rooms.

Complete with an easy-to-fit rigid click system, and with a 1mm thick underlay attached to the boards, laying this floor could not be simpler.

The textured surface follows the grain patterns beneath for an authentic wood look and feel which is warm underfoot and is fully waterproof – making it an ideal choice for bathrooms. It's also blissfully easy to care for; regular vacuuming and occasional damp-mopping are all that's required to ensure it stays looking fabulous.

Spectra Luxury Rigid Core Pearl Oak is soft and beautiful in its design. Gorgeously subtle and contemporary, this versatile oak-look floor will work effortlessly in any room you choose, so you can be sure you've found your match. A rigid limestone core means you don't have to compromise on quality for a durable, hard wearing floor, which is suitable for high traffic areas in the home.

Product Details

Code:	VIN-CLIC-PL-607
Brand:	Spectra
Construction:	Rigid Core (SPC)
Surface:	Embossed In Register
Profile:	Click
Edge profile:	Micro Bevel
Wear layer:	0.3mm
Thickness:	4.5mm + 1mm Integrated underlay
Width:	231mm
Length:	1535mm
Coverage per pack:	2.13m ²
AC rating:	Moderate Commercial

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	32
Fire resistance:	Class Bfl-S1
Formaldehyde emission:	TVOC 44.1 ug (ISO)
Slip resistance:	R10
Thermal resistance/conductivity:	PASS (ISO 105B02)
Wear resistance:	Class 32

Warranty

Residential:	25 Years
Commercial:	15 Years Light Commercial

As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded.
NB: Please ask for full warranty terms and conditions

UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG
Tel: 02476 012 840
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2023. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.